

Technical Data Sheet

CODE 40317

E 604 T ATEX II 2G/D H
T3/125°C X GB/DB



Axial plate-mounted fans for installation in potentially explosive areas



Certifications


CE ATEX-CE

EAC

TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,71	Number of Poles	4
Absorbed Power max (W)	374	Number of speeds	1
Frequency (Hz)	50	Voltage (V)	400
Insulation Class	I°	Weight (Kg)	18,0
IP	65	Delivery max (l/s)	1916,7
Max ambient temperature for continuous operation (°C)	+ 40	Delivery max (m³/h)	6900
Min ambient temperature for continuous operation (°C)	- 20	Pressure max (mmH2O)	20,8
Nominal Diameter (mm)	630	Pressure max (Pa)	203,7
Number of Phases (Ph)	3	RPM	1400
		Sound Pressure level Lp [dB (A)] 3m	75,4

DIMENSIONS



Diametro \emptyset (mm)	630
Size A (mm)	760
Size B (mm)	760
Size C (mm)	340
Size D (mm)	630
Size E (mm)	610
Size F (mm)	598
Size G (mm)	127
Size H (mm)	12
Size L (mm)	15
Size M (mm)	628
Size N (mm)	618

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 40317

E 604 T ATEX II 2G/D H
T3/125°C X GB/DB




Axial plate-mounted fans for installation in potentially explosive areas

DESCRIPTION

- Nominal diameter 600 mm
- Frame with port and grille made of pressed steel, pickled and phosphated, and treated initially with epoxy base coat; thereafter, grey textured finish obtained by applying a coat of polyurethane powder paint strengthened by oven baking.
- 1 speed asynchronous three-phase AC motor with shaft turning in double shielded ball bearings, size to UNEL MEC standard, flange B35, manufactured employing methods and materials suitable for use in environments with potentially explosive atmospheres, according to Explosion Protection standards EN ISO 80079-36:2016; EN 14986:2017.
- Maximum air flow 6,900 m³/h
- Impeller with aluminium hub and blades of antistatic nylon filled with glass fibre.
- Aluminium cooling fan.
- Pressed steel motor cover.
- Metal cable glands for electrical connection.
- IMQ-certified for use in areas at risk of explosion due to presence of gas and dust:
- IMQ 10 ATEX 029 X; GR II cat. 2G/D h T3/125 X

CURVES



ACCESSORIES



GV2 ME04

Code 21113

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com