

PA3210CE08 Air curtain

Electrical heat 8kW, L=1m

Item number: 19801



Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m*
- Horizontal mounting

PA3200C is a compact air curtain for commercial building entrances.

The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation	
Type of installation	Horizontal
Maximum installation height	3,200 mm
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,068 mm
Height	256 mm
Depth	458 mm
Weight	26 kg

Air flow

Air flow	1750; 1450; 1100	m³/h
----------	------------------	------

Sound data

Sound level	57; 52; 46	dB(A)
-------------	------------	-------

Sound power level LWA	72	dB(A)
-----------------------	----	-------

Motor/control supply

Control/motor supply	230	V
----------------------	-----	---

Control/motor current	0.65	A
-----------------------	------	---

Input power (P1), motor	150	W
-------------------------	-----	---

Electric heat

Heat output	8; 5	kW
-------------	------	----

Heat amperage	11.5; 7.2	A
---------------	-----------	---

Heat voltage	400	V
--------------	-----	---

Phases	3N~	
--------	-----	--

Temperature rise, maximum heat output, highest airflow	13	°C
--	----	----

Temperature rise, maximum heat output, lowest airflow	22	°C
---	----	----

Performance

Parameter	
Power	8.00 kW
Air flow	1750 m³/h
Inlet air temperature	20 °C
Outlet air temperature	34 °C
Inlet air humidity	70.0 % r.H
Outlet air humidity	31.3 % r.H

Energy class label

Energy class, Local demand	
Heating	Electrical heat
Built-in heater (kW)	8 kW

Accessories

- PA2DR Remote + door contact (15662)
- PA34TR15 Threaded bars (18056)
- PAMLK PC board alarm (18690)
- PA2P15 Pendulum bar (19568)
- PA3PF15 Pendulum brackets (25256)

Documents

- Catalogue pages PA3200C
- Manual PA3200C
- BPD AIR CURTAIN PA-PL32XXCE.PDF
- Declaration of Conformity PA3200C
- UKCA Declaration PA3200C

Specification

Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m
- Horizontal mounting

Application

PA3200C is a compact air curtain for commercial building entrances. The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

PA3200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

Design

With its timeless design PA3200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.