

Wall mounted unit

FXAQ-A



Home leave operation

For rooms with no false ceilings nor free floor space



Whisper quiet

> Flat, stylish front panel blends easily within any interior décor and is easier to clean



Vertical auto swing

> Can easily be installed in both new and refurbishment projects



Multi tenant

> The air is comfortably spread up- and down-wards thanks to 5 different discharge angles that can be programmed via the remote control

> Maintenance operations can be performed easily from the front of the unit


FXAQ-A



Indoor unit			FXAQ	15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity		kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity		kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	kW	0.02		0.03		0.02	0.03	0.05
	Heating	Nom.	kW	0.03			0.04	0.02	0.04	0.06
Dimensions	Unit	Height	mm	290						
		Width	mm	795				1,050		
		Depth	mm	266				269		
Weight	Unit		kg	12				15		
Casing	Colour			White						
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	8.4/7.0	9.1/7.0	9.4/7.0	9.8/7.0	12.2/9.7	14.4/11.5	18.3/13.5
Air filter	Type			Washable resin net						
Sound power level	Cooling	High/Nom.	dB(A)	51.0/-	52.0/-	53.0/-	55.0/-		58.0/-	63.0/-
Sound pressure level	Cooling	High/Low	dB(A)	32.0/28.5	33.0/28.5	35.0/28.5	37.5/28.5	37.0/33.5	41.0/35.5	46.5/38.5
	Heating	High/Low	dB(A)	33.0/28.5	34.0/28.5	36.0/28.5	38.5/28.5	38.0/33.5	42.0/35.5	47.0/38.5
Refrigerant	Type			R-410A						
	GWP			2,087.5						
Piping connections	Liquid	OD	mm	6,35						9,52
	Gas	OD	mm	12,7						15,9
	Drain			VP13 (I.D. 15/O.D. 18)						
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)	A		16						
Control systems	Infrared remote control			BRC7EA628 / BRC7EA629						
	Wired remote control			BRC1H51W/S/K, BRC1E53A/B/C						

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN18-245

11/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.