



V6FI-60 Floor Standing Unit
Fully caters for the needs of your business!



Avoid Me



Golden Fin



Energy Class



Follow Me



Maximum Air Flow




V6FI-60 / V6FO-60



Anti-Cold Air Function



Low Ambient Cooling at -20°C



Excellent Heating Performance at -15°C



Smart Touch Panel



Smart Controller



24-hour Timer



Auto Swing Louver



Louver Position Memory

Model		V6FI-60 / V6FO-60	
Cooling Capacity (Btu/h)		48.000 (12.000-53.500)	
Cooling Capacity (kWatt)		14.07 (3.52-15.68)	
Heating Capacity (Btu/h)		55.000 (14.000-61.000)	
Heating Capacity (kWatt)		16.12 (4.10-17.88)	
EER		2.84	
COP		3.16	
Seasonal Efficiency (In accordance to EN14825)	Cooling	Pdesign (kW)	14.1
		Energy Class	A++
		SEER	6.1
	Heating (Middle Zone)	Pdesign (kW)	11.1
		Energy Class	A+
		SCOP	4.0
	Heating (Warm Zone)	Pdesign (kW)	11.0
		Energy Class	A+++
		SCOP	5.1
Voltage/Frequency/Phase (V/Hz/Ph)		380-415/50/3	
Current Input (A)	Cooling	8.00 (1.90-10.30)	
	Heating	8.50 (1.90-10.50)	
Power Input (W)	Cooling	4.950 (0.900-5.950)	
	Heating	5.100 (1.000-6.200)	
Air Flow Volume (m³/h)	Indoor unit (High/Medium/Low)	2.413/2.222/2.027	
	Outdoor unit	7.500	
Noise Level [dB(A)]	Indoor unit (High/Medium/Low)	53/49/47	
	Outdoor unit	67	
Sound Power Level [dB(A)]	Indoor unit/ Outdoor unit	67/73	
Power Supply Wire Outdoor / Fuses (Noxmm²)/(A)		5x2.5 / 3x20	
Power Supply Wire Indoor / Fuses (Noxmm²)/(A)		3x1.5 / 1x10	
Signal Wires (Noxmm²)		2 x 1.0 Shielded	
Dimensions (WxDxH) (mm)	Indoor unit	629x456x1.935	
	Outdoor unit	952x415x1.333	
Net Weight (kg)	Indoor/Outdoor Unit	58.4/106.7	
Liquid Line Gas Line		3/8" 5/8"	
Refrigerant/Charge (g)		R32/2.900	
Operation Temperature Range (°C)	Cooling	-15~50	
	Heating	-15~24	