

PERFORMANCE DATA

Model	C-SBN303L8A
Power Source	3-PH 50Hz 380V
Condensing Temp.(°C)	30、35、40、45、50、54.4、60
Suction Gas Temp(°C)	18.3
Sub Cooled(K)	0
Compressor Cooling	Liquid Injection
Refrigerant	R404A

Capacity (W)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	2,150	2,640	4,000	6,050	7,450	9,160	11,270
	35	1,950	2,410	3,660	5,560	6,850	8,440	10,400
	40.0	1,780	2,200	3,340	5,100	6,290	7,760	9,580
	45.0	1,620	2,000	3,060	4,670	5,770	7,140	8,830
	50.0	1,470	1,820	2,790	4,280	5,300	6,560	8,130
	54.4			2,580	3,960	4,920	6,090	7,560
	60.0				3,600	4,470	5,550	6,900

Input (W)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	2,430	2,470	2,520	2,560	2,560	2,570	2,560
	35	2,720	2,750	2,800	2,830	2,840	2,840	2,840
	40.0	3,050	3,080	3,120	3,140	3,150	3,150	3,160
	45.0	3,440	3,450	3,480	3,500	3,500	3,510	3,520
	50.0	3,880	3,880	3,880	3,890	3,900	3,910	3,920
	54.4			4,270	4,280	4,280	4,300	4,310
	60.0				4,810	4,820	4,830	4,860

Current (A)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	4.9	5.0	5.0	5.1	5.1	5.1	5.1
	35	5.3	5.4	5.4	5.5	5.5	5.5	5.5
	40.0	5.8	5.8	5.9	5.9	5.9	5.9	5.9
	45.0	6.3	6.3	6.4	6.4	6.4	6.4	6.4
	50.0	6.9	6.9	6.9	6.9	6.9	6.9	7.0
	54.4			7.4	7.4	7.4	7.4	7.5
	60.0				8.1	8.1	8.1	8.2